



US009592344B2

(12) **United States Patent**  
**Simpson et al.**

(10) **Patent No.:** **US 9,592,344 B2**

(45) **Date of Patent:** **Mar. 14, 2017**

(54) **MEDICAL CONNECTOR WITH INTERNAL VALVE MEMBER MOVABLE WITHIN MALE LUER PROJECTION**

(71) Applicant: **ICU Medical, Inc.**, San Clemente, CA (US)

(72) Inventors: **Philip J. Simpson**, Escondido, CA (US); **Walter D. Gillespie**, San Diego, CA (US); **David G. Matsuura**, Encinitas, CA (US)

(73) Assignee: **ICU Medical, Inc.**, San Clemente, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/169,606**

(22) Filed: **May 31, 2016**

(65) **Prior Publication Data**  
US 2016/0271327 A1 Sep. 22, 2016

**Related U.S. Application Data**  
(63) Continuation of application No. 14/052,592, filed on Oct. 11, 2013, which is a continuation of application (Continued)

(51) **Int. Cl.**  
*A61M 5/31* (2006.01)  
*A61M 39/26* (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... *A61M 5/31* (2013.01); *A61M 5/3134* (2013.01); *A61M 39/10* (2013.01); *A61M 39/22* (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC ..... A61M 39/10; A61M 39/22; A61M 39/26; A61M 2039/2473; A61M 2039/2486;  
(Continued)

(56) **References Cited**  
**U.S. PATENT DOCUMENTS**  
2,842,382 A 7/1958 Franck  
2,931,668 A 4/1960 Baley  
(Continued)


**FOREIGN PATENT DOCUMENTS**  
CA 2747283 A1 7/2002  
EP 0 158 030 10/1985  
(Continued)

**OTHER PUBLICATIONS**  
International Search Report and Written Opinion dated Jun. 28, 2005.  
(Continued)

*Primary Examiner* — Kami A Bosworth  
(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson & Bear, LLP

(57) **ABSTRACT**  
Disclosed herein is a valve assembly comprising a male luer end portion and a female luer end portion and a passage for the transfer of fluids extending between the male and female luer end portions, valve means movable between a first position, in which the passage is closed, and a second position, in which the passage is open, biasing means for biasing the valve means toward the first position, and actuating means extending into the male luer end portion and coupled to the valve means to actuate the valve means when a female luer end portion of a medical accessory is engaged with the male luer end portion.

**34 Claims, 15 Drawing Sheets**



**Related U.S. Application Data**

- No. 13/305,663, filed on Nov. 28, 2011, now Pat. No. 8,556,868, which is a continuation of application No. 12/789,255, filed on May 27, 2010, now Pat. No. 8,066,692, which is a continuation of application No. 10/584,920, filed as application No. PCT/US2004/042723 on Dec. 21, 2004, now Pat. No. 7,758,566.
- (60) Provisional application No. 60/532,916, filed on Dec. 30, 2003.
- (51) **Int. Cl.**  
*A61M 39/10* (2006.01)  
*A61M 39/22* (2006.01)  
*A61M 5/14* (2006.01)  
*A61M 5/168* (2006.01)  
*A61M 5/34* (2006.01)
- (52) **U.S. Cl.**  
 CPC ..... *A61M 39/26* (2013.01); *A61M 5/14* (2013.01); *A61M 5/16881* (2013.01); *A61M 5/34* (2013.01); *A61M 2005/3103* (2013.01); *A61M 2005/3128* (2013.01); *A61M 2039/1033* (2013.01); *A61M 2039/1066* (2013.01); *A61M 2205/19* (2013.01)
- (58) **Field of Classification Search**  
 CPC ..... A61M 2039/261; A61M 2039/262; A61M 2039/263; A61M 2039/267; A61M 2039/268; A61M 2005/3128  
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,968,497 A 1/1961 Treleman  
 3,127,892 A 4/1964 Bellamy, Jr. et al.  
 3,304,047 A 2/1967 Martin  
 3,334,860 A 8/1967 Bolton, Jr.  
 3,707,972 A 1/1973 Villari et al.  
 3,729,031 A 4/1973 Baldwin  
 3,986,508 A 10/1976 Barrington  
 4,055,179 A 10/1977 Manschot et al.  
 4,066,067 A 1/1978 Micheli  
 4,076,285 A 2/1978 Martinez  
 4,080,965 A 3/1978 Phillips  
 4,084,606 A 4/1978 Mittleman  
 4,121,585 A 10/1978 Becker, Jr.  
 4,133,441 A 1/1979 Mittleman et al.  
 4,143,853 A 3/1979 Abramson  
 4,150,845 A 4/1979 Kopacz et al.  
 4,195,632 A 4/1980 Parker et al.  
 4,233,982 A 11/1980 Bauer et al.  
 4,245,635 A 1/1981 Kontos  
 4,324,239 A 4/1982 Gordon et al.  
 4,334,551 A 6/1982 Pfister  
 4,340,049 A 7/1982 Munsch  
 4,379,458 A 4/1983 Bauer et al.  
 4,387,879 A 6/1983 Tauschinski  
 4,397,442 A 8/1983 Larkin  
 4,430,073 A 2/1984 Bemis et al.  
 4,436,125 A 3/1984 Blenkush  
 4,457,749 A 7/1984 Bellotti et al.  
 4,511,359 A 4/1985 Vaillancourt  
 4,538,836 A 9/1985 Kruetten  
 4,610,469 A 9/1986 Wolff-Mooij  
 4,619,640 A 10/1986 Potolsky et al.  
 4,623,332 A 11/1986 Lindmayer et al.  
 4,629,159 A 12/1986 Wellenstam  
 4,660,803 A 4/1987 Johnston et al.  
 4,662,878 A 5/1987 Lindmayer  
 4,700,744 A 10/1987 Rutter et al.  
 4,723,603 A 2/1988 Plummer  
 4,728,075 A 3/1988 Paradis

4,745,950 A 5/1988 Mathieu  
 4,774,964 A 10/1988 Bonaldo  
 4,774,965 A 10/1988 Rodriguez et al.  
 4,781,702 A 11/1988 Herlli  
 4,804,015 A 2/1989 Albinsson  
 4,816,024 A 3/1989 Sitar et al.  
 4,819,692 A 4/1989 Olson et al.  
 4,834,271 A 5/1989 Litwin  
 4,862,913 A 9/1989 Wildfang  
 4,883,483 A 11/1989 Lindmayer  
 4,915,687 A 4/1990 Sivert  
 4,917,669 A 4/1990 Bonaldo  
 4,935,010 A 6/1990 Cox et al.  
 4,950,260 A 8/1990 Bonaldo  
 D313,277 S 12/1990 Haining  
 D314,050 S 1/1991 Sone  
 5,006,114 A 4/1991 Rogers et al.  
 5,021,059 A 6/1991 Kensey et al.  
 5,047,021 A 9/1991 Utterberg  
 5,065,783 A 11/1991 Ogle, II  
 5,070,885 A 12/1991 Bonaldo  
 5,098,385 A 3/1992 Walsh  
 5,108,376 A 4/1992 Bonaldo  
 5,122,123 A 6/1992 Vaillancourt  
 5,139,483 A 8/1992 Ryan  
 5,147,333 A 9/1992 Raines  
 5,154,703 A 10/1992 Bonaldo  
 RE34,223 E 4/1993 Bonaldo  
 5,199,948 A 4/1993 McPhee  
 5,201,725 A 4/1993 Kling  
 5,203,775 A 4/1993 Frank et al.  
 5,211,634 A 5/1993 Vaillancourt  
 5,215,537 A 6/1993 Lynn et al.  
 5,215,538 A 6/1993 Larkin  
 5,242,393 A 9/1993 Brimhall et al.  
 5,242,425 A 9/1993 White et al.  
 5,251,873 A 10/1993 Atkinson et al.  
 5,269,771 A 12/1993 Thomas et al.  
 5,273,533 A 12/1993 Bonaldo  
 5,279,571 A 1/1994 Larkin  
 5,281,206 A 1/1994 Lopez  
 5,284,475 A 2/1994 Mackal  
 5,295,657 A 3/1994 Atkinson  
 5,301,686 A 4/1994 Newman  
 5,306,243 A 4/1994 Bonaldo  
 5,312,377 A 5/1994 Dalton  
 5,324,270 A 6/1994 Kayan et al.  
 5,330,450 A 7/1994 Lopez  
 5,334,159 A 8/1994 Turkel  
 5,344,414 A 9/1994 Lopez et al.  
 5,360,413 A 11/1994 Leason et al.  
 5,370,636 A 12/1994 Von Witzleben  
 5,380,306 A 1/1995 Brinon  
 5,385,372 A 1/1995 Utterberg  
 5,390,898 A 2/1995 Smedley et al.  
 5,391,150 A 2/1995 Richmond  
 5,395,348 A 3/1995 Ryan  
 5,397,314 A 3/1995 Farley et al.  
 5,400,500 A 3/1995 Behnke et al.  
 5,401,245 A 3/1995 Haining  
 5,402,826 A 4/1995 Molnar et al.  
 5,402,982 A 4/1995 Atkinson et al.  
 5,405,323 A 4/1995 Rogers et al.  
 5,405,331 A 4/1995 Behnke et al.  
 5,405,333 A 4/1995 Richmond  
 5,411,499 A 5/1995 Dudar et al.  
 5,417,673 A 5/1995 Gordon  
 5,423,791 A 6/1995 Bartlett  
 5,425,465 A 6/1995 Healy  
 5,433,330 A 7/1995 Yatsko et al.  
 5,439,451 A 8/1995 Collinson et al.  
 5,441,487 A 8/1995 Vedder  
 5,445,623 A 8/1995 Richmond  
 5,447,177 A 9/1995 Ricken et al.  
 5,456,668 A 10/1995 Ogle, II  
 5,456,675 A 10/1995 Wolbring et al.  
 5,462,255 A 10/1995 Rosen et al.  
 5,464,399 A 11/1995 Boettger  
 5,470,319 A 11/1995 Mayer

(56)

References Cited

U.S. PATENT DOCUMENTS

5,470,327	A	11/1995	Helgren et al.	6,290,206	B1	9/2001	Doyle
5,474,536	A	12/1995	Bonaldo	6,299,132	B1	10/2001	Weinheimer et al.
5,480,393	A	1/1996	Bommarito	6,402,207	B1	6/2002	Segal et al.
5,489,274	A *	2/1996	Chu .....	6,428,520	B1	8/2002	Lopez
			A61M 39/0613	6,431,219	B1	8/2002	Redler et al.
			604/167.05	6,485,472	B1	11/2002	Richmond
5,492,147	A	2/1996	Challender et al.	6,499,719	B1	12/2002	Clancy et al.
5,501,426	A	3/1996	Atkinson et al.	6,508,792	B2	1/2003	Szames et al.
5,507,744	A	4/1996	Tay et al.	6,508,807	B1	1/2003	Peters
5,514,177	A	5/1996	Kurz et al.	6,541,802	B2	4/2003	Doyle
5,518,026	A	5/1996	Benjey	6,543,745	B1	4/2003	Enerson
5,520,665	A	5/1996	Fleetwood	6,581,906	B2	6/2003	Pott et al.
5,520,666	A	5/1996	Choudhury et al.	6,585,229	B2	7/2003	Cote et al.
5,527,284	A	6/1996	Ohnemus et al.	6,595,964	B2	7/2003	Finley et al.
5,533,708	A	7/1996	Atkinson et al.	6,595,981	B2	7/2003	Huet
5,533,983	A	7/1996	Haining	6,609,696	B2	8/2003	Enerson
5,535,785	A	7/1996	Werge et al.	6,612,624	B1	9/2003	Segal et al.
5,540,661	A	7/1996	Tomisaka et al.	6,666,852	B2	12/2003	Niedospial, Jr.
5,549,566	A	8/1996	Elias et al.	6,695,817	B1	2/2004	Fangrow
5,549,577	A	8/1996	Siegel et al.	6,745,998	B2	6/2004	Doyle
5,549,651	A	8/1996	Lynn	6,840,501	B2	1/2005	Doyle
5,552,118	A	9/1996	Mayer	6,869,426	B2	3/2005	Ganem
5,555,908	A	9/1996	Edwards et al.	6,875,205	B2	4/2005	Leinsing
5,569,235	A	10/1996	Ross et al.	6,899,315	B2	5/2005	Mailville et al.
5,573,516	A	11/1996	Tyner	6,955,669	B2	10/2005	Curutcharry
5,575,769	A	11/1996	Vaillancourt	6,964,406	B2	11/2005	Doyle
5,578,059	A	11/1996	Patzer	7,004,934	B2	2/2006	Vaillancourt
5,584,819	A	12/1996	Kopfer	7,037,302	B2	5/2006	Vaillancourt
5,591,137	A	1/1997	Stevens	7,040,598	B2	5/2006	Raybuck
5,591,143	A	1/1997	Trombley, III et al.	7,044,441	B2	5/2006	Doyle
5,597,536	A	1/1997	Mayer	7,100,891	B2	9/2006	Doyle
5,616,129	A	4/1997	Mayer	7,125,396	B2	10/2006	Leinsing et al.
5,616,130	A	4/1997	Mayer	7,137,654	B2	11/2006	Segal et al.
RE35,539	E	6/1997	Bonaldo	7,140,592	B2	11/2006	Phillips
5,643,224	A	7/1997	Szapiro et al.	7,182,313	B2	2/2007	Doyle
5,645,538	A	7/1997	Richmond	7,195,228	B2	3/2007	Tiberghien et al.
5,674,206	A	10/1997	Allton et al.	7,244,249	B2	7/2007	Leinsing et al.
5,676,346	A	10/1997	Leinsing	7,306,197	B2	12/2007	Parrino et al.
5,685,868	A	11/1997	Lundquist	7,306,198	B2	12/2007	Doyle
5,699,821	A	12/1997	Paradis	7,306,566	B2	12/2007	Raybuck
5,700,248	A	12/1997	Lopez	7,347,458	B2	3/2008	Rome et al.
5,702,374	A	12/1997	Johnson	7,350,764	B2	4/2008	Raybuck
5,709,243	A	1/1998	Wells et al.	7,361,164	B2	4/2008	Simpson et al.
5,735,826	A	4/1998	Richmond	7,497,484	B2	3/2009	Ziman
5,738,144	A	4/1998	Rogers	7,559,530	B2	7/2009	Korogi et al.
5,749,861	A	5/1998	Guala et al.	7,588,563	B2	9/2009	Guala
RE35,841	E	7/1998	Frank et al.	7,645,274	B2	1/2010	Whitley
5,782,816	A	7/1998	Werschmidt et al.	7,651,481	B2	1/2010	Raybuck
5,785,693	A	7/1998	Haining	7,666,170	B2	2/2010	Guala
5,806,831	A	9/1998	Paradis	7,758,566	B2	7/2010	Simpson et al.
5,814,024	A	9/1998	Thompson et al.	7,766,304	B2	8/2010	Phillips
5,820,601	A	10/1998	Mayer	7,766,897	B2	8/2010	Ramsey et al.
5,839,715	A	11/1998	Leinsing	7,803,139	B2	9/2010	Fangrow, Jr.
5,848,994	A	12/1998	Richmond	7,815,614	B2	10/2010	Fangrow, Jr.
5,947,954	A	9/1999	Bonaldo	7,837,658	B2	11/2010	Cote et al.
6,029,946	A	2/2000	Doyle	7,857,805	B2	12/2010	Raines
6,036,171	A	3/2000	Weinheimer et al.	7,976,532	B2	7/2011	Kitani et al.
6,039,302	A	3/2000	Cote, Sr. et al.	8,066,692	B2	11/2011	Simpson et al.
6,041,805	A	3/2000	Gydesen et al.	8,177,772	B2	5/2012	Christensen et al.
6,050,978	A	4/2000	Orr et al.	8,211,069	B2	7/2012	Fangrow et al.
6,063,062	A	5/2000	Paradis	8,225,826	B2	7/2012	Horppu et al.
6,068,011	A	5/2000	Paradis	8,262,628	B2	9/2012	Fangrow, Jr.
6,068,617	A	5/2000	Richmond	8,286,936	B2	10/2012	Kitani et al.
6,079,432	A	6/2000	Paradis	8,287,513	B2	10/2012	Ellstrom et al.
6,106,502	A	8/2000	Richmond	8,454,579	B2	6/2013	Fangrow, Jr.
6,113,068	A	9/2000	Ryan	8,556,868	B2	10/2013	Simpson et al.
6,142,446	A	11/2000	Leinsing	8,721,628	B2	5/2014	Ziman
6,152,913	A	11/2000	Feith et al.	9,114,242	B2	8/2015	Fangrow et al.
6,168,137	B1	1/2001	Paradis	9,168,366	B2	10/2015	Fangrow et al.
6,170,522	B1	1/2001	Tanida	9,345,641	B2	5/2016	Krause et al.
6,171,287	B1	1/2001	Lynn et al.	9,358,379	B2	6/2016	Fangrow
6,189,859	B1	2/2001	Rohrbough et al.	2003/0066978	A1	4/2003	Enerson
6,206,860	B1	3/2001	Richmond	2003/0136932	A1	7/2003	Doyle
6,224,578	B1	5/2001	Davis et al.	2003/0208165	A1	11/2003	Christensen et al.
6,242,393	B1	6/2001	Ishida et al.	2004/0074541	A1	4/2004	Sharpe
6,245,048	B1	6/2001	Fangrow et al.	2004/0124388	A1	7/2004	Kiehne
				2004/0124389	A1	7/2004	Phillips
				2004/0244848	A1	12/2004	Maldavs
				2005/0015075	A1	1/2005	Wright et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0124942	A1	6/2005	Richmond
2005/0228362	A1	10/2005	Vaillancourt
2006/0025751	A1	2/2006	Roy et al.
2006/0058734	A1	3/2006	Phillips
2006/0065873	A1	3/2006	Doyle
2006/0129109	A1	6/2006	Shaw et al.
2006/0142730	A1	6/2006	Proulx et al.
2006/0142735	A1	6/2006	Whitley
2006/0149213	A1	7/2006	Raybuck
2006/0157984	A1	7/2006	Rome et al.
2006/0161115	A1	7/2006	Fangrow
2006/0202146	A1	9/2006	Doyle
2006/0253084	A1	11/2006	Nordgren
2007/0043334	A1	2/2007	Guala
2007/0088292	A1	4/2007	Fangrow
2007/0088293	A1	4/2007	Fangrow
2007/0088294	A1	4/2007	Fangrow
2007/0088327	A1	4/2007	Guala
2007/0179453	A1	8/2007	Lim et al.
2008/0103485	A1	5/2008	Kruger
2008/0190485	A1	8/2008	Guala
2008/0290657	A1	11/2008	McKeon, III
2009/0177170	A1	7/2009	Kitani et al.
2010/0063482	A1	3/2010	Mansour et al.
2010/0174242	A1	7/2010	Anderson et al.
2010/0253070	A1	10/2010	Cheon et al.
2011/0306931	A1	12/2011	Kamen et al.
2012/0031515	A1	2/2012	Whitaker
2012/0089101	A1	4/2012	Carlyon et al.
2012/0316536	A1	12/2012	Carrez et al.
2013/0035668	A1	2/2013	Kitani et al.
2013/0317483	A1	11/2013	Reichart et al.
2015/0051555	A1	2/2015	Fangrow, Jr.
2016/0213910	A1	7/2016	Fangrow, Jr. et al.
2016/0263367	A1	9/2016	Fangrow et al.

FOREIGN PATENT DOCUMENTS

EP	0 368 473	A2	5/1990
EP	0 791 371		8/1997
EP	0 795 342		9/1997
EP	1 946 792		7/2008
GB	2 116 277		9/1983
GB	2 118 440		11/1983
GB	2 353 078		2/2001
JP	56-72659		6/1981
JP	59-41429		3/1984
JP	59-138532		8/1984
JP	60-89488		6/1985
JP	63-175383		11/1988
JP	11-311234		11/1999
JP	2004-000483	A	1/2004
JP	2001-187990	A	7/2007

WO	WO 95/32748	12/1995
WO	WO 01/03756	1/2001
WO	WO 01/23026	4/2001
WO	WO 02/096500	12/2002
WO	WO 03/013646	2/2003
WO	WO 2004/060474	7/2004
WO	WO 2004/082756	9/2004
WO	WO 2006/076656	7/2006
WO	WO 2006/088858	8/2006
WO	WO 2006/124756	11/2006
WO	WO 2007/008511	1/2007
WO	WO 2007/112944	10/2007
WO	WO 2008/144447	11/2008
WO	WO 2010/071848	8/2010
WO	WO 2011/139995	11/2011
WO	WO 2013/036854	3/2013

OTHER PUBLICATIONS

U.S. Appl. No. 14/020,579, Oct. 22, 2015, Fangrow et al.  
 International Search Report for International Application No. PCT/US2004/042723, Notification mailed on Sep. 9, 2004 in 5 pages.  
 International Written Opinion of International Application No. PCT/US2004/042723 issued on Jul. 3, 2006 in 10 pages.  
 Air Embolism and Exsanguination from Separation of Two-Piece Side Port/Hemostasis Valve Cardiac Catheter Introducers, ECRI Institute, Jan. 1995 in 2 pages, [http://www.mdsr.ecri.org/summary/detail.aspx?doc\\_id=8098](http://www.mdsr.ecri.org/summary/detail.aspx?doc_id=8098).  
 EPO Examination Report re EP Application No. 08 755 612.2, dated Nov. 20, 2013 in 5 pages.  
 EPO Examination Report re EP Application No. 08 755 612.2, dated Dec. 5, 2012 in 6 pages.  
 EPO Search Report re EP Application No. 08 755 612.2, dated Feb. 23, 2012 in 5 pages.  
 Injection Site, Molded Products, Inc., Apr. 2, 2004 in 1 page, <https://web.archive.org/web/20040402123354/https://www.moldedproducts.com/injectionsite.htm>.  
 International Preliminary Report on Patentability and Written Opinion for PCT/US2006/026124, dated Jan. 10, 2008 in 11 pgs.  
 International Preliminary Report on Patentability, International Application No. PCT/US2008/063797 mailed on Nov. 17, 2009 in 11 pages.  
 International Search Report and Written Opinion of International Application No. PCT/US2004/042723 issued on Jun. 28, 2005 in 16 pages.  
 International Search Report of International Application No. PCT/US2004/042723 issued on Jun. 28, 2005 in 5 pages.  
 International Search Report and Written Opinion of International Application No. PCT/US2008/063797 mailed on Dec. 30, 2008 in 21 pages.  
 International Search Report for PCT/US2006/026124, dated Mar. 3, 2007 in 5 pgs.

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3





FIG. 4






FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12






FIG. 13




FIG. 14




FIG. 15

**MEDICAL CONNECTOR WITH INTERNAL  
VALVE MEMBER MOVABLE WITHIN MALE  
LUER PROJECTION**

CROSS-REFERENCE TO RELATED  
APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 14/052,592, filed Oct. 11, 2013, which is a continuation of U.S. patent application Ser. No. 13/305,663, filed Nov. 28, 2011, now U.S. Pat. No. 8,556,868, which is a continuation of U.S. patent application Ser. No. 12/789,255, filed May 27, 2010, now U.S. Pat. No. 8,066,692, which is a continuation of U.S. patent application Ser. No. 10/584,920, filed Dec. 28, 2006, now U.S. Pat. No. 7,758,566, which is the National Stage Entry of International Application No. PCT/US04/42723, filed Dec. 21, 2004, which claims the benefit of U.S. Provisional Application No. 60/532,916, filed Dec. 30, 2003; the entire contents of all of which are hereby incorporated by reference herein and made a part of this specification. Any and all priority claims identified in the Application Data Sheet, or any correction thereto, are hereby incorporated by reference under 37 CFR 1.57.

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to medical fluid delivery valves and more particularly to valve assemblies for use with syringes or other medical dispensing devices.

Description of the Related Art

Syringes are commonly used to deliver medications and other biological fluids to a patient. The syringe typically has a plunger which is sealingly engaged with an outer cylindrical chamber to form an inner fluid-receiving chamber. A 'male' luer fitting is usually provided at a delivery end of the chamber which receives a female luer fitting with a needle assembly or the like. The fluid channel joining the cavity to the luer fitting is usually open, so that when the needle is removed, the cavity is open to the environment. This is problematic since many medications and biological fluids are sensitive (or can degrade when exposed) to the environment.

It is therefore an object of the present invention to provide a novel valve assembly for use with a syringe or other medical dispensing devices, enabling the latter to be closed to the environment when in an unattached condition.

SUMMARY OF THE INVENTION

In one of its aspects, the present invention provides a valve assembly comprising a male luer end portion, a female luer end portion and a channel for the transfer of fluids between the male and female luer end portions, valve means movable between a closed position and an open position, biasing means for biasing the valve means toward the closed position, and actuating means extending into the male luer end portion and coupled to the valve means to actuate the valve means when a female luer end portion of a medical accessory is coupled with the male luer end portion.

In an embodiment the male luer end portion has an inner projection and outer threaded sheath which is spaced therefrom to receive the female luer end portion therebetween. The actuating means includes an actuating member positioned between the outer threaded sheath and the inner projection.

In an embodiment, the valve means includes a valve seat and a valve member moveable relative thereto. The channel includes a first channel portion adjacent the female luer end portion and the inner projection includes a second channel portion. The valve member has a valve channel portion in fluid communication with the first and second channel portions. The valve seat is formed in the second channel portion and the valve member is integrally formed with the female luer end portion.

In one embodiment, the valve member includes an anchor flange extending outwardly toward an inner surface of the housing portion. In this case, the housing portion is coupled to the male luer end portion for movement therewith relative to the valve member. The male luer end portion engages the anchor flange when the valve means is in the closed position and the male luer end portion is spaced from said anchor flange when the valve means is in the open position. The housing portion terminates at an end region adjacent the female luer end portion, the biasing means includes a compression spring located within the housing between the end region and the outer anchor flange.

In another of its aspects, the present invention provides a medical dispensing device comprising a body having a chamber therein to contain a fluid material, a valve assembly in fluid communication with the chamber, the valve assembly having a male coupling member for engaging a female coupling member on a medical accessory to form a fluid coupling between the medical dispensing device and the medical accessory, the valve assembly further comprising flow control means operable to control fluid flow through the male coupling member, the flow control means being operable to be displaced by the female coupling member to open the male coupling member when female coupling member is operatively connected therewith, the flow control means being operable to be displaced by the female coupling member to close the male coupling member when the female coupling member is disconnected therefrom.

In one embodiment, the male coupling member includes an inner male portion and an outer sheath portion spaced therefrom to form a passage there between for receiving the female coupling member, the flow control means including at least one valve actuating portion positioned in the passage to abut the female coupling member and to displace the valve member during the travel of the female coupling member along the passage. The valve assembly includes a valve member and a valve seat, wherein the valve member is positioned against the seat to close the male coupling member. The valve actuating portion includes a pair of abutment elements which are spaced from one another along the passage to receive the female coupling member there between, wherein the pair of abutment elements are operable to travel with the female coupling member along the passage.

In one embodiment, the actuating portion is longitudinally oriented relative to the passage and the abutment elements are positioned along the actuating portion.

The valve member includes a back plate and a plurality of actuating portions equally spaced on the back plate, each of the actuating portions having first and second abutment elements.

In one embodiment, the valve actuating portion includes a locking flange which is adjacent one of the abutment elements. The valve assembly includes a locking seat to receive the locking flange when the male coupling member is in the closed position. The actuating portion has a distal end region, the locking flange being located adjacent the distal end region and the locking seat is formed in the outer

3

sheath portion. The actuating portion is thus arranged to flex in order to displace the locking flange from the locking seat.

In yet another aspect, the present invention provides a medical dispensing device comprising a body having a chamber therein to contain a fluid material, a valve assembly in fluid communication with the chamber, the valve assembly having a male coupling member for engaging a female coupling member on a medical accessory to form a fluid coupling between the medical dispensing device and the medical accessory, the male coupling member including a projection and an outer valve member movable relative to the projection, the projection and the outer valve member forming a fluid channel there between, a sheath portion encircling the projection and spaced therefrom to form a passage to receive the female coupling member, the valve member being engageable with the female coupling member and movable relative to the projection to open the fluid channel when the female coupling member is connected with the male coupling member.

In one embodiment, the valve member forms an outer surface of the male coupling portion.

In an embodiment, biasing means is provided to bias the valve member toward an engaged position with the projection to close the fluid channel. In this particular case, the passage ends at an inner wall and the biasing means includes a spring located between the inner wall and the valve member.

In one embodiment, the projection is fixed to the body and includes an inner passage, the inner passage having one end which is open to the chamber and another end which is open to the fluid channel. The projection also includes an enlarged end portion, the valve member including an outer portion arranged to engage the enlarged end portion to close the fluid channel. In this case the enlarged end portion and the outer end portion on the valve member have mating bevelled surfaces.

In one embodiment, the female coupling member has a leading segment, the valve member being dimensioned to fit within the leading segment.

Preferably, the medical dispensing device includes such items as a syringe, an IV bottle, an IV line, a powder and/or atomized fluid and/or gas inhalant dispenser, an implant delivery dispenser, a ventilator, a syringe pump, an intubation tube, a gastrointestinal feeding tube or a plurality and/or a combination thereof.

Preferably, the medical material is in solid, liquid or gaseous form or a combination thereof and has beneficial properties to enhance life, to promote health, to cure and/or treat a disease, condition or ailment, to monitor and/or indicate a bodily function or a combination thereof. For example, the medical material may be useful for, among others, IV therapy, implantation, stem cell therapy, oncology therapy, blood transfusion and/or organ transplantation.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Several preferred embodiments of the present invention will now be described, by way of example only, with reference to the appended drawings in which:

FIG. 1 is a perspective view of a syringe assembly;

FIG. 2 is a sectional view of a portion of the assembly of FIG. 1;

FIGS. 3 and 4 are sectional views of the assembly of FIG. 1 in two alternate operative positions;

FIG. 5 is a fragmentary sectional perspective view of a portion of another syringe assembly;

4

FIGS. 6 and 7 are fragmentary perspective views of another syringe assembly;

FIGS. 8 to 12 are fragmentary sectional views of the syringe assembly of FIG. 6;

FIG. 13 is a fragmentary perspective view of yet another syringe assembly; and

FIGS. 14 and 15 are fragmentary sectional views of the syringe assembly of FIG. 13 or portions thereof.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to the figures, and in particular FIG. 1, there is provided a syringe assembly 10 comprising a syringe 12 and a valve unit 14. The syringe 12 has a chamber 20 containing a plunger 22 to form a cavity 24. Referring to FIG. 2, the cavity has an outlet 26 and the valve unit 14 is located downstream of the outlet 26 for coupling the cavity 24 with a medical accessory such as a needle 30 (as shown in FIGS. 3 and 4). The valve unit 14 has an outlet 32 and flow control means, as will be described, to control fluid flow through the outlet, the flow control means being operable to open the outlet when the coupling section is operatively connected with the medical accessory, the flow control means being operable to close the outlet when the valve unit is disconnected from the medical accessory and to remain closed until connected once again with a medical accessory.

In this case, the chamber 20 includes a first male luer end portion 34 adjacent the outlet 26 and the valve unit 14 includes a first female luer end portion 36 which is engageable with the male luer end portion 34. The valve unit 14 also includes a second male luer end portion 38 for coupling with the medical accessory 30.

Although the chamber 20 and the valve unit 14 are separate from one another in this case, it will be understood that they may, alternatively, be integrally formed, for example by combining the first male luer end portion 34 with the female luer end portion 36.

The valve unit 14 has a channel 42 for the transfer of fluids between the female and male luer end portions 36, 38. A valve means, in the form of a valve member 44 is located in the valve unit 14 and is movable between a first position (as shown in FIG. 2), in which the channel is closed, and a second position (as shown in FIG. 3), in which the channel is open. An actuating means, in the form of an actuating member 46 (shown in FIG. 2), extends outwardly from the valve member 44 and into the male luer end portion 38. The actuating member 46 is coupled to the valve member 44 to actuate it when a female luer end portion of the medical accessory 30 is engaged with the male luer end portion 38.

In the embodiment of FIGS. 1 to 4, the male luer end portion 38 has an outer threaded sheath 50 which is spaced from an inner projection 52. In this case, the actuating member 46 is positioned between the outer threaded sheath 50 and the inner projection 52. The valve member 44 includes a valve plug portion 54 moveable relative to a valve seat portion 56. The valve member 44 has an upper end which is integrally formed with the female luer end portion 36. An outer housing member 58 is slidably mounted on the valve member 44. In this case, the outer housing member 58 is joined to the male luer end portion 38. The valve member 44 also has a valve channel 44a extending from the female luer end portion 36 to the valve plug portion 54 where it terminates at one or more transverse flow openings 44b to join with the channel 42.

The valve member 44 includes an anchor flange 60, and the male luer end portion 38 seats, directly or indirectly,

5

against the anchor flange 60 when the valve is in the closed position as viewed in FIG. 2. Conversely, the male luer end portion 38 is spaced from said anchor flange when the valve is in the open position as shown in FIG. 3.

The outer housing 58 terminates at a radially inwardly directed end region 62 adjacent the female luer end portion 34 and a biasing means in the form of a compression spring 64 is located within the outer housing between the end region 62 and the anchor flange 60 to bias the valve member toward the first position to close the valve unit.

An alternative arrangement is shown in FIG. 5. In this case, the valve unit 70 has a housing 72 which is integrally formed with the female luer end portion 74. A first channel portion 76 is adjacent the female luer end portion 74 and a second channel portion 78 is adjacent a male luer end portion 80. In this case, the valve means includes a valve member 82 having a valve channel 84 in fluid communication with the first and second channel portions 76 and 78. In this case, the valve seat portion is formed at 90 in the second channel portion 78.

The valve member 82 includes a plug portion 92 which is movable relative to and within the second channel portion 78 for engaging the seat portion 90 to close the second channel portion 78. The first channel portion 76 includes a tubular projection 94 extending from the female luer end portion 74. In this case, the valve channel 84 in the valve member 82 is coextensive with the first and second channel portions 76, 78. In this case, the tubular projection 94 is slidably engaged with the valve member 82 within the valve channel 84 and sealed therein by way of seal 98. Likewise, the valve member 84 is sealed within the second channel portion 78 by way of seal 100.

The syringe assembly 10 is used as follows. First, the valve unit 14 is joined to the syringe 12 by engaging the corresponding first male luer end portion 34 with the female luer end portion 36. In this condition, the second male luer end portion 38 is unattached with a medical accessory such as the needle 30 and the actuator 46 is fully extended into the second male luer end portion 38 as shown in FIG. 2. Consequently, the valve member 44 is biased to its closed position, thereby engaging the valve plug portion 54 against the valve seat 56.

The needle 30 is then attached to the syringe by engaging the female luer end portion on the needle 30 with the second male luer end portion 38. Doing so causes the female luer end portion on the needle 30 to abut and displace the actuating member 46, thereby causing the valve member 44 to be displaced upwardly (as viewed in FIG. 2) thereby releasing the valve plug portion 54 from its sealed abutment with the valve seat 56 to open the valve channel. The plunger 22 may then be displaced outwardly to cause fluids in the proximity of the pointed end of the needle 30 to be drawn into the cavity 24, by a path starting at the valve seat 56 through the channel 42 to the transverse flow openings 44b, to the valve channel 44a and on through the female luer end portion and into the cavity 24. The needle 30 may then be removed causing the actuating member 46 to be displaced downwardly (as viewed in FIG. 2) causing the immediate displacement of the valve plug portion to abut the seat 56 and thereby close the valve.

Another device is shown at 120 FIGS. 6 to 12, having a body 122 forming an inner chamber 124 therein to contain a fluid material. A valve assembly 126 is in fluid communication with the chamber 124 and has a male coupling member 128 for engaging a female coupling member 130 on a medical accessory (in this case a needle 132) to form a fluid coupling between the device 120 and the needle 132.

6

The valve assembly 126 is operable to control fluid flow through the male coupling member 128 and more particularly to be in an open position when the male coupling member 128 is operatively connected with the female coupling member 130 and, conversely, to be in a closed position when the male coupling member 128 is disconnected from the female coupling member 130.

In this case, the body 122 and the valve assembly 126 are integrally formed and, as seen in FIG. 8, the latter includes a valve member 134 and a valve seat 136. The valve member 134 is shown in its position against the valve seat 136 to close the male coupling member 128, but for a very minor gap there between for illustrative purposes only.

The male coupling member 128 includes an inner male portion 140 having an inner fluid channel 140a and an outer sheath portion 142 spaced from the inner male portion 140 to form a passage 144 there between for receiving the female coupling member 130. At least one, in this case three, valve actuating portions 146 (two being shown in FIG. 7) are positioned in the passage 144 to abut the female coupling member 130 and to displace the valve member during the travel of the female coupling member 130 along the passage 144. In this case, each valve actuating portion 146 is integrally formed with the valve member 134.

Each valve actuating portion 146 includes a pair of abutment elements 150, 152 which are spaced from one another along the passage 144 to receive the female coupling member 130 there between and to travel with the female coupling member along the passage 144. The abutment element 152 has a bevelled outer surface 152a for reasons to be described. Each actuating portion 146 is longitudinally oriented relative to the passage 144 and the abutment elements 150, 152 are positioned along the actuating portion 146.

Each valve actuating portion 146 includes a locking flange 154 and the valve assembly includes a locking seat 156 to receive the locking flange 154 when the valve member 134 is in the closed position. In this case, the valve actuating portion 146 has a distal end region and the locking flange 154 is located in the distal end region, while the locking seat 156 is formed in the outer sheath portion 142.

It will be seen in FIG. 10 that each valve actuating portion 146 is arranged to flex in order to displace the locking flange 154 out of the locking seat 156.

Referring to FIG. 8, the valve member 134 includes a back plate 160 and the actuating portions 146 are equally spaced on the back plate 160. The back plate 160 has a central fluid channel 162 which is in fluid communication with the chamber 124 and the valve member 134 has a fluid channel 163 therein in fluid communication with the central fluid channel 162 and hence the chamber 124. In addition, the fluid channel 163 has a lateral portion 163a which establishes fluid communication between the fluid channel 163 and an inner fluid channel 140a in the inner male portion.

The device 120 is thus used as follows. The valve assembly is set with the valve member in its closed position, that is with the valve member 134 in its position against the valve seat 136 as shown in FIG. 8. The female coupling member 130 on the needle 132 is aligned with the passage 144 and brought toward the male coupling member 128. The bevelled leading surface 152a on the abutment member 152 aids to centre the female coupling member on the mouth of the passage 144. With the locking flange 154 in the locking seat 156, the female coupling member 130 is able to pass the lowermost edge of the abutment element 152 and continue into the passage 144 until the female coupling member

makes contact with the abutment element **150** as seen in FIG. **9**. As seen in FIG. **10**, continued inward force on the female coupling member is transferred to the abutment element **150** causing the abutment portion **146** to move inwardly along the passage and thus to draw the locking flange **154** from this locked position in the locking seat **156**, causing the abutment portion **146** to flex, until the locking flange **154** is removed from the locking seat **156**. At this position, it can be seen that the valve member **134** has moved from the valve seat **136** to open the fluid channel **163** to the needle **132**.

Referring to FIG. **11**, as the female coupling member **130** is removed from the passage **144**, it makes contact with the abutment element **152** and causes the abutment portion **146** to move outwardly along the passage **144** and thus cause the valve member **134** to move toward the valve seat **136**. The locking flange **154** approaches, and finally enters, the locking seat **156** to coincide with the closure of the valve assembly.

Thus, the device **120** does not make use of a valve member which is biased to its closed position as with the earlier embodiment, but rather relies on the displacement of the female coupling member **130** to draw the valve assembly to its closed position when it is removed from the male coupling member **128**.

Another device is shown at **170** in FIGS. **13** to **15**, having a body **172** providing a chamber **174** therein to contain a fluid material. A valve assembly **176** is in fluid communication with the chamber **174** and has a male coupling member **178** for engaging a female coupling member **180**, again on a needle **181**, to form a fluid coupling between the medical dispensing device **170** and the needle **181**.

The valve assembly **176** is operable to control fluid flow through the male coupling member and more particularly to actuate or open the male coupling member **178** when operatively connected with the female coupling member **180** and, conversely, to close the male coupling member **178** when disconnected from the female coupling member **180**.

In this case, the male coupling member **178** includes a projection **182** which is fixed to the body **172**. A sheath portion **184** encircles the projection **182** and is also fixed to the body **172**. The sheath portion **184** and is spaced from the projection **182** to form a passage **186** to receive the female coupling member **180**.

A valve member **190** is movable relative to the projection **182** and forms a fluid channel **192** there between and sealed by an inner seal **193**. The projection **182** includes an inner passage **194** which has one end **194a** open to the chamber **174** and another end **194b** which is open to the fluid channel **192**.

Referring to FIGS. **14** and **15**, the projection includes an enlarged end portion **198** and the valve member **190** has an outer portion **200** arranged to engage the enlarged end portion **198** to close the fluid channel **192**. In this case, the passage **186** ends at an inner wall **202** and the valve member **190** is movable relative to the inner wall **202** under the action of a spring **203** which is positioned in the passage **186** between the valve member **190** and the inner wall **202** to bias the outer end portion **200** of the valve member **190** toward an engaged position with the enlarged end portion **198**.

As can be seen in FIG. **15**, the enlarged end portion **198** and the outer end portion **200** of the valve member **190** have mating bevelled surfaces **198a** and **200a** respectively.

The valve member **190** is operable to engage the female coupling member **180** and to travel with the female coupling member **180** along the passage **186**. In this case, the female

coupling member **180** has a leading segment **180a** and the outer end portion **200** of the valve member **190** is dimensioned to fit within the leading segment **180a**.

In contrast to the device **120** of FIG. **6**, the device **170** has a valve member **190** which is biased to the closed position. As the female coupling member **180** passes over the projection **182**, the leading segment **180a** of the female coupling member **180** rides over the outer end portion **200** of the valve element **190**. Continued inward displacement of the female coupling member **180** into the passage **186** thus causes the valve member to move relative to the projection **182** until the mating bevelled surfaces **198a**, **202a** separate to open the fluid channel **192** to the needle. The fluid coupling is thus fully operational when the female and male coupling members are tightly engaged. When the female coupling member **180** is removed from the male coupling member **178**, the valve member **190** is returned to its closed position against the projection **198** under the biasing action of the spring **203**, to close the male coupling member.

While the present invention has been described for what are presently considered the preferred embodiments, the invention is not so limited. To the contrary, the invention is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

The valve unit may be used with other medical fluid delivery devices, such as IV lines, catheters, infusion pumps and the like. The valve unit may also be used on syringes and other medical devices which do not employ the ubiquitous luer coupling arrangement.

The following is claimed:

1. A medical connector configured to receive a male luer end of a syringe, the medical connector comprising:
  - an exterior surface, an interior region, proximal and distal housing portions, and proximal and distal ends, wherein the proximal and distal housing portions form at least a portion of the exterior surface of the connector and wherein the proximal and distal housing portions are separate from each other and coupled together, the proximal housing portion extending further in a proximal direction than the distal housing portion, and the distal housing portion extending further in a distal direction than the proximal housing portion;
  - a female luer in the proximal housing portion of the connector, the female luer configured to receive the male luer end of the syringe into the proximal end of the connector;
  - a male luer projection in the distal housing portion of the connector, the male luer projection comprising interior and exterior surfaces, and proximal and distal ends, the interior surface of the male luer projection comprising a first region with a first cross-sectional width and a second region with a second cross-sectional width, the first cross-sectional width being smaller than the second cross-sectional width;
  - a threaded sheath surrounding a portion of the male luer projection;
  - a sheath cavity positioned between the exterior surface of the male luer projection and an inner surface of the threaded sheath, the sheath cavity having a proximal end and a distal end;
  - a valve member being longitudinally movable between a closed position and an open position, the valve member comprising: (i) an internal fluid pathway, (ii) a first portion positioned outside of the male luer projection in

both the open and the closed positions, and (iii) a second portion distal from the first portion;

the second portion of the valve member comprising: (i) transverse openings, (ii) a distal plug portion with curved sidewalls that are distal from the transverse openings, the distal plug portion being closed in both the open and closed positions so as to obstruct fluid communication between an interior region of the male luer projection and the internal fluid pathway of the valve member in the closed position, and (iii) a distal-most end tip that is positioned distal of the proximal end of the sheath cavity in the closed position; and

a seal that, in the closed position, contacts a portion of the valve member that is within the distal housing portion in a seal-contacting region of the valve member with only straight sidewalls, said seal-contacting region being located in a proximal direction from the curved sidewalls of the distal plug portion of the valve member, the seal being located within the distal housing portion in a proximal direction from both the first and second regions on the interior surface of the male luer projection;

wherein the valve member is biased toward the closed position.

2. The medical connector of claim 1, wherein the distal-most end tip of the second portion of the valve member is flat.

3. The medical connector of claim 2, wherein the distal-most end tip of the second portion of the valve member is flush with the distal end of the male luer projection in the closed position.

4. The medical connector of claim 1, wherein the connector comprises two seals.

5. The medical connector of claim 1, wherein the curved sidewalls of the distal plug portion contact the interior surface of the male luer projection in the closed position.

6. The medical connector of claim 1, wherein the valve member moves in a proximal direction to transition from the closed position to the open position.

7. A combination of the medical connector of claim 1 and the syringe.

8. A medical connector comprising:

- a housing comprising an exterior surface, an interior region, proximal and distal regions, and proximal and distal ends;
- a female luer in the proximal region of the housing that is integral with the housing;
- a male luer projection in the distal region of the housing that is integral with the housing, the male luer projection comprising interior and exterior surfaces, and proximal and distal ends;
- a threaded sheath surrounding a portion of the male luer projection;
- a sheath cavity positioned between the exterior surface of the male luer projection and an inner surface of the threaded sheath, the sheath cavity having a proximal end and a distal end;
- a valve member that is separate from the female luer, the valve member being movable between a closed position and an open position, the valve member comprising: (i) an internal fluid pathway, (ii) a first portion, and (iii) a second portion distal from the first portion, wherein the first portion of the valve member is positioned outside of the male luer projection in both the open and closed positions;

the second portion of the valve member comprising: (i) at least one transverse opening; (ii) a distal plug portion

with curved sidewalls that are distal from the at least one transverse opening, the distal plug portion being closed in both the open and closed positions so as to obstruct fluid communication between an interior region of the male luer projection and the internal fluid pathway of the valve member in the closed position, and (iii) a distalmost end tip that is positioned distal of the proximal end of the sheath cavity in the closed position, wherein a portion of an outer surface of the second portion of the valve member proximal from the curved sidewalls of the distal plug portion is positioned adjacent to a portion of the interior surface of the male luer projection in the closed position; and

a seal that contacts the valve member;

wherein the valve member is biased toward the closed position.

9. The medical connector of claim 8, wherein the outer surface of the second portion of the valve member contacts the interior surface of the male luer projection in the closed position.

10. The medical connector of claim 8, wherein the second portion of the valve member is positioned within the interior region of the connector in both the open and closed positions.

11. The medical connector of claim 8, wherein the valve member moves in a proximal direction to transition from the closed position to the open position.

12. A medical connector comprising:

- a housing comprising an exterior surface, an interior region, proximal and distal regions, and proximal and distal ends;
- a male luer projection in the distal region of the housing, the male luer projection comprising an exterior surface, an interior region, and proximal and distal ends;
- a valve member movable longitudinally between a closed position and an open position, the valve member being made of a single piece of material, and the valve member comprising a hollow interior with an internal fluid pathway, a proximal end of the internal fluid pathway of the valve member being located, in the closed position, within a portion of a proximal region of the connector that is configured to retain a male luer end of a syringe in the open position, wherein a distal end tip of the valve member is narrower than a transverse width of the interior region of the male luer projection, the distal end tip being positioned inside of the interior region of the male luer projection in the closed position to obstruct fluid communication between the interior region of the male luer projection and the internal fluid pathway of the valve member in the closed position; and
- a seal portion positioned closer to the distal end of the housing than to the proximal end of the housing, the seal portion contacting the valve member, the seal portion extending around a portion of the valve member in both the open and closed positions, a distal end of the hollow interior of the valve member extending distally beyond the seal portion;

wherein the valve member is biased toward the closed position.

13. The medical connector of claim 12, wherein a portion of an outer surface of the valve member adjacent to the distal end tip is positioned adjacent to a portion of an interior surface of the male luer projection in the closed position.



## 11

14. The medical connector of claim 12, wherein there is no seal portion positioned in a distal direction from the distal end tip of the valve member in either the open or closed positions.

15. The medical connector of claim 12, wherein in the closed position the distal end tip of the valve member is flush with the distal end of the male luer projection.

16. The medical connector of claim 12, wherein the connector comprises separate proximal and distal housing portions that are attached together.

17. The medical connector of claim 16, wherein the seal portion is located within the distal housing portion.

18. The medical connector of claim 12, wherein the valve member moves in a proximal direction to transition from the closed position to the open position.

19. The medical connector of claim 12, wherein a proximal end of the valve member is configured to receive the male luer end of the syringe.

20. A combination of the medical connector of claim 12 and the syringe.

21. A medical connector configured to receive a male luer end of a syringe, the medical connector comprising:

a housing comprising an exterior surface, an interior region, separate proximal and distal regions that are attached to each other and form at least a portion of the exterior surface of the medical connector, and proximal and distal ends, the proximal region of the housing comprising a proximal half and a distal half, the proximal half comprising a maximum outer cross-sectional width, a minimum outer cross-sectional width, and a transverse outer annular region proximal from the maximum outer cross-sectional width;

a male luer projection in the distal region of the connector housing, the male luer projection comprising interior and exterior surfaces, and proximal and distal ends;

a threaded sheath surrounding a portion of the male luer projection;

a sheath cavity positioned between the exterior surface of the male luer projection and an inner surface of the threaded sheath, the sheath cavity having a proximal end and a distal end;

a valve member movable between a closed position and an open position, the valve member comprising a proximal first portion and a second portion distal from the first portion, the first and second portions of the valve member being formed of a single piece of material, and the first and second portions of the valve member being configured to move longitudinally between the closed and open positions such that a proximal end of the first portion is positioned more proximally the closed position than the transverse outer annular region of the proximal half of the proximal region;

the first portion of the valve member being positioned outside of the male luer projection in the closed position, and a distal end tip of the second portion of the valve member being positioned distal of the proximal end of the sheath cavity in the closed position;

## 12

the valve member further comprising an internal fluid pathway, and a distal plug portion that is closed in both the open and closed positions, the plug portion being part of the second portion of the valve member, and the plug portion being configured to obstruct fluid communication between an interior region of the male luer projection and the internal fluid pathway of the valve member in the closed position;

a seal portion contacting the valve member, the seal portion positioned adjacent to where the proximal and distal regions of the housing are attached to each other, the seal portion extending around the valve member in both the open and closed positions; and wherein the valve member is biased toward the closed position.

22. The medical connector of claim 21, wherein the distal plug portion of the valve member remains within the male luer projection in both of the open and closed positions.

23. The medical connector of claim 21, wherein the distal plug portion of the second portion of the valve member is positioned in a distal direction from the seal portion in both of the open and closed positions.

24. The medical connector of claim 21, wherein a proximal end of the internal fluid pathway is located radially within a proximal threaded region of the connector in the open position.

25. The medical connector of claim 21, wherein the proximal first portion of the valve member is configured to contact the syringe in the open position.

26. The medical connector of claim 21, wherein a portion of an outer surface of the second portion of the valve member proximally adjacent to the distal plug portion contacts a portion of the interior surface of the male luer projection in the closed position.

27. The medical connector of claim 26, wherein there is no seal portion positioned in a distal direction from the distal plug portion of the second portion of the valve member in either the open or closed positions.

28. The medical connector of claim 27, wherein the first portion of the valve member comprises a female luer end portion.

29. The medical connector of claim 21, wherein an exterior surface of the connector comprises a minimum cross-sectional width of the exterior surface of the connector that is located in the proximal region of the connector.

30. The medical connector of claim 21, wherein in the closed position the distal plug portion of the valve member is flush with the distal end of the male luer projection.

31. The medical connector of claim 21, wherein the proximal and distal regions are attached to each other in an overlapping region.

32. The medical connector of claim 31, wherein the seal portion is located within the distal housing portion.

33. The medical connector of claim 21, wherein the valve member moves in a proximal direction to transition from the closed position to the open position.

34. A combination of the medical connector of claim 21 and the syringe.

\* \* \* \* \*